

## Jan/2019 Free 721Q 400-051 PDF Instant Download from Braindump2go[Q222-Q232]

**January/2019 Braindump2go 400-051 Exam Dumps with PDF and VCE New Updated Today! Following are some new 400-051 Real Exam Questions:]**

**QUESTION 222**In Cisco IOS routers, which chipset is the PVDM2-32 DSP hardware based on?A. C5441B. C549C. C5510D. C5421E. Broadcom 1500**Answer: C**

**QUESTION 223**Which two analog telephony signaling methods are most vulnerable to glare conditions? (Choose two.)A. FXS Loop-startB. FXO Ground-startC. E&M Wink-startD. E&M Delay-dialE. E&M Immediate-startF. E&M Feature Group D**Answer: A**

**Explanation:**The loop start signaling method is more common and is typically used by residential phone lines. When a voice port is configured with loop start signaling, the device (telephone) closes the circuit loop that signals the CO voice port to provide dial tone; an incoming call is signaled on the CO by supplying a predefined voltage on the line. The loop start signaling method has one main disadvantage in that it has no method of preventing both sides of the connection from attempting to seize the line at the same time; this condition is referred to as glare. Because of this, loop start signaling is typically not used on high demand circuits. With immediate-start, the calling side of the connection seizes the line by going off hook on the Ellead and address information is sent using dual-tone multifrequency (DTMF) digits. Immediate start signaling is vulnerable to glare just like loop-start signaling.

**QUESTION 224**Which digital modulation method is used to transmit caller ID information on analog FXS ports on Cisco IOS routers?A. DTMFB. PSK C. FSKD. MF E. pulse dialing**Answer: C**

**QUESTION 225**How many signaling bits are there in each T1 time slot using channel associated signaling with Super Frame?A. 1B. 2C. 4D. 8E. 12**Answer: B**

**QUESTION 226**What is the maximum one-way delay, in milliseconds, between any two Cisco Unified Communications Manager servers in a non-Session Management Edition cluster over an IP WAN?A. 20B. 40C. 80D. 160E. 250**Answer: B**

**QUESTION 227**Which design restriction applies to Cisco Unified Communications Manager Session Management Edition clustering over the WAN deployment with extended round-trip times in Cisco Unified CM 9.1 and later releases?A. SIP and H.323 intercluster trunks are supported.B. Only SIP trunk is supported.C. SIP trunks and H.323 gateways are supported.D. A minimum of 1.544 Mb/s bandwidth is required for all traffic between any two nodes in the cluster.E. Only RSVP agents can be configured and registered to the SME cluster as media resources.**Answer: B**

**QUESTION 228**Which Cisco Unified Communications Manager deployment model for clustering over the IP WAN mandates a primary and a backup subscriber at the same site?A. multisite with centralized call processingB. multisite with distributed call processingC. local failoverD. remote failoverE. remote failover with Cisco Unified Communications Manager Express as SRST**Answer: C**

**QUESTION 229**Refer to the exhibit. All displayed devices are registered to the same Cisco Unified Communications Manager server and the phones are engaged in an active call. Assume that the provided configurations exist at the phone line level and multicast MOH is disabled cluster wide. Which description of what will happen when the user of IP phone A presses the Hold soft key is true?A. IP phone B receives audio source 2 from MOH server A.B. IP phone B receives audio source 3 from MOH server A.C. IP phone B receives audio source 2 from MOH server B.D. IP phone B receives audio source 3 from MOH server B.E. IP phone B receives audio source 1 from MOH server A.**Answer: C**

**QUESTION 230**Refer to the exhibit. What is the maximum number of inbound calls to 2001 before a Cisco Unified Communications Manager Express system returns user busy tone to any additional calls? A. 3B. 4C. 5D. 6E. 7**Answer: D**

**QUESTION 231**When calls are placed by certain Cisco Unified Communications Manager supplementary services, the Local Route Group feature will be bypassed. Which of these does not belong to the supplementary services?A. Call BackB. Call ForwardC. Message Waiting indicatorD. Mobility Follow Me E. Path Replacement**Answer: B**

**QUESTION 232**Which statement about whisper intercom implementation on Cisco Unified Communications Manager is correct?A. Only one-way audio exists from the calling to the called party.B. The speaker volume on the called phone will be reduced automatically to avoid disturbance to other users nearby.C. The called party auto-answers the call in headset mode.D. Only one-way audio exists from the called to the calling party.E. Whisper Intercom is visual only, there is no audio.**Answer: A**

2019 Latest 400-051 Exam Dumps (PDF & VCE) 721Q&As Download:  
<https://www.braindump2go.com/400-051.html>2.2019 Latest 400-051 Exam Questions & Answers Download:  
<https://drive.google.com/drive/folders/0B75b5xYLjSSNWGtttXZ3UGRqWjQ?usp=sharing>